



HIVE™

Programmable Receiver with Display

Stand Alone - 800 or 1600 Memory



FEATURES

- 800 or 1600 User Memory (single entry or block coded)
- 800' Range (open range test w/extended antenna kit)
- 2 Channels (2 relays)
- 318 MHz or MHz Rolling Code Technology
- 2 Line, 16 Character LED Display
- Individual Transmitter Deletion (Frees up space in memory)
- Menu Driven, Plain English Programming



SPECIFICATIONS

Carrier frequency: 433.92MHz
Local oscillator freq: 6.6128 MHz
Power supply: 12/24 Vac/dc
Modulation: AM/ASK
Number of memorizable users: 1600
Number of relays: 2
Type of output contact: 1 NO, 1 NO/NC
Commutable power: 24VA
Maximum relay voltage: 60V
Absorbtion: 95 mA
Housing protection: IP40
Operating temperature: 14 °F to 131 °F
Overall dimensions: 7.08 x5.51x 2.67 in
Weight: 11.35 oz.

ACCESSORIES

- Stingray 433MHz
- Monarch 433MHz



2480 South 3850 West, Suite B
Salt Lake City, UT 84120
(866) 975-0101 • (866) 975-0404 fax
www.transmittersolutions.com

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.