

Bug Barrier® AUTOMATIC Roll-Up

AUTOMATIC OPERATION ~

In-tube motor is rated at 4 amps, single phase 120 v. Constant contact switch activates motor. Door speed is approximately 12" per second. (See page #8 for High Cycle usage)

Maximum 16' wide and 16' high

Minimum width ~ 40"

MOUNTING OPTIONS ~

Header Mount, Face of Wall, Stand-Off Bracket Mount and E-Track Mount. Unit width is critical on all header mounted doors. All Bug Barriers® are manufactured to + or - 1/8" tolerance.

SCREEN ~

Standard green color - other colors available. 17" x 11" high strength, vinyl coated polyester weave screen material. Windbars are reinforced in yellow safety vinyl.

BREAKAWAY FEATURE ~

Fiberglass windbars remain flexible enough to pop out in case of accidental impact. Optional aluminum hinges available with bottom profile breakaway system for additional wind load.

HEAD ROOM ~

6" to 8" will be used for header mount application. 8" is needed above the door opening for wall mount application. 18" will be required for aluminum hinge option.

TRACKS ~

2" wide and 2" deep Snaptite aluminum tracks. Header mount will take up to 2-1/2" of side room on each side. Wall mount will take up to 6" of side room on each side. Doors 11' wide and over will require 4" deep Snaptite tracks. Optional 6" deep track for additional wind load.

WEATHERSTRIPPING ~

Grey vinyl weatherstripping is angled to provide a tighter seal preventing bugs and insects easy access or entry. Optional brush seal available.

RESET SYSTEM ~

Interlocking brush seal is incorporated at the top of the Snaptite tracks causing a reset system. Should the door be forced out of the tracks by accidental impact, the door is designed to reset back into the guides.

One year warranty on parts and workmanship.



Aluminum Hinge Option