PROGRAMMING YOUR NEW TRANSMITTER

1. Open the case, as shown.



For code setting:
Open your existing transmitter,
or the cover on receiver located
on your operator and follow the
steps corresponding to your
brand of garage door opener.
Then re-close the cover.


WARNING

If this transmitter tirggers other garage doors in your neighbourhood, change all your transmitters and receiver to a new code setting.

DO NOT let children use the garage door transmitter without adult supervision. Children can injure themselves or others by the garage door.

FOR MULTI-CODE® & STANLEY® OPERATORS (300MHZ)

- 1. Use a pen to set the DIP switches to '+' (positive), '0' (middle),
- You do not need to relocate 'CODE' and 'FREQ' jumper for Stanley @and Multi-Code @ (300 MHZ) operators.




WARRANTY

If, within one year from date of purchase, this product should become defective (except battery), due to faulty workmanship or materials, it will be repaired or replaced, without charge. Proof of purchase is required.

FOR MULTI-CODE® & STANLEY® OPERATORS (310MHZ)

For Stanley[®], Multi-code[®](310 MHZ) operators. Insert the jumper to cover the 'FREQ' two pins but DO NOT relocate the 'CODE' jumper block.



FCC

The Garage Door Remote Control is approved by the FCC and it complies with Part 15 of the FCC Rules. Its operation is subject to the following two conditions:

- 1. This device may not cause harmful interference.
- This device must accept any interference that may cause undesired operation.

FOR LINEAR®, or MOORE-O-MATIC® OPERATORS (310MHZ)

- Use a pen to set the DIP switches to match the code of your existing transmitter or receiver. The last two switches are not used for Linear[®] and Moore-O-Matic[®] operators.
- 2. Insert the jumper to cover the 'FREQ' two pins and insert the 'CODE' jumper to the lower two pins.





Skylink will not be liable or responsible for any misuse or application of this product other than for its intended use.

SKYLINK Technobgies Inc., P.O. Box 35002, 3355 The Collegeway, Mississauga, Ontario L5L 5W8 CANADA (905)568-2095 (905)568-3923 FAX Customer Service: (800)304-1187 EST 9:00 to 17:00 http://www.sky-link.org Patent no.: D377458, 5841390, 5680134

Patents Pending ©1993 SKYLINK TECHNOLOGIES INC. 101A110 REV 0 Mar, 99

BATTERY

12 volt "cigarette lighter" type (size 23A) battery (included).



GARAGE DOOR REMOTE CONTROL USER'S INSTRUCTIONS (MODEL 100)

